



# WEEDELETE®

## Hoeing machines

RELIABLE



DAMAGE-FREE

ECOLOGICAL



HIGH QUALITY

### WEEDELETE® RS

This mechanical hoeing machine hoes both between and in the rows of the trees. It also takes obstacles and drip hoses into account.



### WEEDELETE® ZRS

This intra-row weeder is meant to hoe blackstrips in tree nurseries, sparing the grass strips in the paths. The ZRS-series can be optionally coupled to the front or the rear of the tractor.



Van Tuijl Innovations B.V.  
Tolsestraat 8A  
4043 KB Opheusden (NL)

+ 31(0) 488 759009  
[info@vti.nl](mailto:info@vti.nl)  
[www.vti.nl](http://www.vti.nl)

# WEEDELETE® RS

“Sold worldwide in  
more than 12 countries”



WEEDELETE® RS	Working width minimum	Working width maximum	Machine width (transport)	Machine weight
RS 80-Z2	100 cm	140 cm	93 cm	± 340 kg
RS 100-Z2	124 cm	164 cm	116 cm	± 372 kg
RS 130-Z2	147 cm	187 cm	139 cm	± 412 kg
RS 150-Z2	170 cm	210 cm	162 cm	± 445 kg

# WEEDELETE® ZRS

“Innovated from the  
practice in cooperation  
with tree growers”

WEEDELETE® ZRS	Working width minimum	Working width maximum	Machine width (transport)	Machine weight
Hydraulic working width adjustment (100 cm)	145 cm	320 cm	125 cm	± 355 kg
Manual working width adjustment (90 cm)	120 cm	285 cm	100 cm	± 318 kg

- The swing rotors can be supplied with rotor hoes of Ø25 cm or Ø30 cm.
- Every ZRS-version is available mounted in front of or behind the tractor, with single or double hoe arm.
- Several options: grass edge cutter, adjustable support wheels, sliding probe and adjustable probe sensitivity.

## Important WEEDELETE® information

- Minimum hydraulic output 20 liters
- Minimum required power 25 HP
- Suitable for all soil types
- Easily adjustable
- Great opportunities
- Levelling effect of the soil
- Maximum working speed of 5 km per hour
- The working speed depends on the planting distance in the row

